

PowerBrick SC

PowerBrick SC is a low-voltage product designed for household energy storage scenarios with a stylish and elegant appearance. It uses a high-capacity 314Ah battery to support 50 parallel units with a capacity range from 16.07kWh to 803.5kWh. It provides a highly safe, reliable, intelligent and friendly experience. Built-in display screen, check the battery status at any time.



Flexible Expansion

Up to 50 units in parallel,
16.07kWh--803.84kWh capacity



Automatic Self-heating

-20°C to 55°C operating
temperature (optional)



Ultra Safe

Intelligent fire extinguishing system,
detects and extinguishes fire in 5s



Easy Installation

Supports wall-mounted and
floor-mounted installations, easy to
move by one person with wheels



Long-term Reliability

LFP cells, 8000+ cycles



Smart Management

Built-in display screen, check the battery
status at any time. real-time system
monitoring, remote control, OTA updates

Model	PowerBrick SC
Battery Type	LiFePO ₄ (LFP)
Nominal Battery Energy	16.076kWh
Usable Battery Energy	15.272kWh
Nominal Capacity	314Ah
Nominal Voltage	51.2V
Operating Voltage	44.8V~57.6V
Recommended Charge & Discharge Current	140A
Max. Charge Current	200A
Max. Discharge Current	200A
Peak Discharge Current (25°C)	300A, 2min
Recommended Charge & Discharge Power	7.168kW
Max. Charge Power	10.24kW
Max. Discharge Power	10.24kW
Depth of Discharge (DOD)	95%
Charge Temp. Range	0°C~55°C/-20°C~55°C(optional)
Discharge Temp. Range	-20°C~55°C
Net Weight	116Kg
Dimension[W/D/H]	435/233/857mm
Protection Level	IP20
Communication	CAN/RS485
Cycle Life ^[1]	≥8000 Cycles
User Interface	WIFI+APP, LCD
Safety Protection	Built-in aerosol fire extinguisher
Installation	Floor-mounted,Wall-mounted
Regulating wheel (4pcs)	1kg,80/80/80(optional)
Top cover	2kg,422/232/60(optional)
Expansion	Up to 50 units in parallel
Certification & Safety Standard	UN38.3/IEC62619
Compatible Inverters	SMA/Victron Energy/Ingeteam/Solis/GoodWe/Growatt/Solplanet/Luxpower/Deye/Apsystem etc.

[1] Test conditions: 0.2C Charging& Discharging, 25°C, 95% DOD, 70%EOL

